

PORTABOQUILLAS


- Snap-on pipe connection with Clip-Eyelet ball-type spray tips
- Ball-type tips allow quick and accurate adjustment of spray direction without disturbing pipe connection
- Use with 1", 1-1/4", 1-1/2" or 2" pipe
- Inlet sizes for 9/16" (14.5 mm) or 21/32" (17 mm) dia. drill holes; retrofit seals are available for 27/32" (21 mm) dia. drill holes
- Chemical- and corrosion-resistant material withstands high temperatures
- Spring-grade stainless steel single- and double-clamp versions
- Optional threaded ball for use with conventional nozzles
- Optional blank spray tip to stop the liquid flow
- Ideal for cleaning, coating and rinsing

See pages 11 to 12 for performance data.

SPECIFICATIONS

Body Assemblies	Double-Clamp Body	Single-Clamp Body	Threaded Ball for Standard Nozzles	Cap Seal	Retrofit Seal	Blank Tip
To fit 9/16" (14.5 mm) or 21/32" (17 mm) dia. drilled inlet openings	For pressures to 150 psi (10.3 bar)	For pressures to 60 psi (4 bar)	For nozzles with 1/4" male connection CP20582-1/4-PPB (NPT) CPB20582-1/4-PPB (BSPT)	CP7717-2/ 121-EPR	For headers with 27/32" (21 mm) dia. holes CP20580-BU SEAL, BUNA-N CP20580-VI SEAL, Viton	CT PLUG – PP
			For nozzles with 3/8" male connection CP20582-3/8-PPB (NPT) CPB20582-3/8-PPB (BSPT)	CP7717-2/ 121-VI, Viton®		

DIMENSIONS & WEIGHTS

20570	Clip-Eyelet Assembly No.	Color-Coded Body	Color-Coded Cap	To Clamp On	Dimensions			Net Weight
					A	B	C	
	20570__-1-PP	Medium Gray	Light Gray	1" pipe	1-3/4" (44 mm)	2-7/8" (73 mm)	1-7/8" (48 mm)	2.7 oz. (.08 kg)
	20570__-1-1/4-PP	Medium Gray	Light Gray	1-1/4" pipe	1-7/8" (48 mm)	3-1/16" (78 mm)	1-7/8" (48 mm)	2.7 oz. (.08 kg)
	20570__-1-1/2-PPB	Black	Light Gray	1-1/2" pipe	2" (51 mm)	3-3/16" (81 mm)	1-7/8" (48 mm)	3.2 oz. (.09 kg)
	20570__-2-PPB	Black	Light Gray	2" pipe	2-3/8" (60 mm)	3-7/16" (87 mm)	1-15/16" (49 mm)	3.2 oz. (.09 kg)

Based on largest/heaviest version of each type.

ORDERING INFORMATION

CLIP-EYELET NOZZLE ASSEMBLY AND SPRAY TIP

ASSEMBLY					SPRAY TIP			
Nozzle Type	Clamp Design*	Inlet Dia.**	Pipe Size	Material Code	Tip Type	Spray Angle	Capacity Size	Mat. Code

Example

20570 D L - 1 - PP + CT 40 10 - PP

*Clamp Design — (no designation) indicates Single Clamp; **D** indicates Double Clamp **Inlet Dia. — (no designation) indicates 9/16" (14.5 mm) dia.; **L** indicates 21/32" (17 mm) dia.

BOQUILLA 6530

3.0 gpm (11.8 l/min)

PERFORMANCE DATA: STANDARD ANGLE

Spray Angle at 40 psi (3 bar)						Capacity Size	Spray Tip Color	Capacity – gallons per minute (liters per minute)									
15°	25°	40°	50°	65°	80°			5 psi (0.3 bar)	10 psi (1 bar)	20 psi (2 bar)	30 psi (3 bar)	40 psi (4 bar)	60 psi (5 bar)	80 psi (6 bar)	100 psi (7 bar)	125 psi (8 bar)	150 psi (10 bar)
	•	•	•	•		30	Orange	1.1 (3.7)	1.5 (6.8)	2.1 (9.7)	2.6 (11.8)	3.0 (13.7)	3.7 (15.3)	4.2 (16.8)	4.7 (18.1)	5.3 (19.3)	5.8 (22)

30	Orange	0.181 (4.6)	2.1 (7.5)	3.0 (13.7)	4.2 (19.3)	5.2 (24)	6.0 (27)	7.3 (31)	8.5 (34)	9.5 (36)	9.5 (39)	11.6 (43)	149°	169°	178°
----	--------	----------------	--------------	---------------	---------------	-------------	-------------	-------------	-------------	-------------	-------------	--------------	------	------	------

